


名称	LEDダウンライト 埋込穴φ150 調光対応 電球色	
型名	EM6D-150U-27R1	
光源	型名	-
	全光束	- [lm] -
保守率	良い	0.81
	普通	0.76
	悪い	0.71
効率	上半球	0 [%]
	下半球	100 [%]
	全方向	100 [%]
器具光束	760 [lm]	



◎配光特性 [cd/1000lm]

$\theta$	$\phi$	a-a'	b-b'	c-c'
0°		767		
10°		730		
20°		607		
30°		396		
40°		217		
50°		122		
60°		78		
70°		45		
80°		18		
90°		0		
100°		0		
110°		0		
120°		0		
130°		0		
140°		0		
150°		0		
160°		0		
170°		0		
180°		0		

照明率表

反射率 (%)	天井						70						50				30		20		0			
	壁		70		50		30		70		50		30		50		30		30		10		0	
室指数	床		30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
0.6	照明率 (×0.01) 初期値																							
0.8	76	70	64	61	56	55	74	69	63	60	56	54	62	59	55	54	55	54	55	54	50	49		
1	85	77	73	69	65	63	83	76	72	68	65	62	70	67	64	62	62	61	61	57	56			
1.25	92	83	81	75	73	69	90	82	79	74	72	69	77	73	71	68	69	68	64	62				
1.5	99	88	88	81	80	75	96	87	86	80	79	75	83	78	77	74	75	73	70	68				
2	104	91	94	85	86	80	101	90	91	84	85	79	88	82	82	78	80	77	74	72				
2.5	110	96	102	91	95	87	107	95	99	90	93	86	95	88	90	85	87	84	81	79				
3	115	99	107	95	101	91	111	98	105	94	99	91	99	92	95	89	92	88	85	84				
4	118	101	111	97	106	94	114	100	108	96	104	94	103	94	99	92	95	91	89	87				
5	121	103	116	100	112	98	117	102	113	99	109	97	106	97	103	95	99	94	92	90				
10	123	104	119	102	115	100	119	103	115	101	112	99	109	99	106	98	101	96	94	92				

